



The new Agatec RL110 offers fast and simple leveling features for professionals.

The combination of innovative engineering and design coupled with durable materials makes the Agatec RL110 the perfect laser for the most demanding construction sites. Featuring fast, electronic self leveling (H/V), three rotation speeds, spot mode, varible scanning function, H.I. alert system and manual slope capabilities, the RL110 is the complete laser tool for a wide variety of applications at the best investment. Ideal for installing drop ceilings, drywall installation, plumb and square applications and general jobsite leveling Agatec RL110 is a complete laser tool for a wide set of interior and exterior applications.

- ±1 mm accuracy at 10 m
- Easy to operate with single-function buttons.
- Complete package with remote control and laser receiver
- Longest battery life: up to 160 hours



Agatec RL110 scope of delivery



The Agatec BCP technology (Brushless Core Power) delivers the highest battery life time and minimal product maintenance.



Agatec SAS – Part of Hexagon Group 21 Bd Littré, 78600 Le Mesnil le Roi, France Tel. +33 1 34 93 35 80 - Fax +33 1 34 93 35 89 info@agatec.com - www.agatec.com



| SPECIFICATIONS | Art. No. 781033 |
|-----------------------------|------------------------------------|
| Range (diameter) | Up to 60 m (200 ft) w/out receiver |
| | Up to 200m (656 ft) w/ receiver |
| Accuracy | ± 1 mm at 10 m (+/- 1/8" at 100ft) |
| Automatic Self-Leveling | Horizontal/Vertical |
| Self-leveling Range | ± 10%; 6° |
| Rotation Speeds | 0, 300, 450, 600 rpm |
| Scanning Angle | Variable from 2° to 36° |
| Laser Diode Type | 635 nm (red) |
| | Class 3R, <5 mW |
| Battery life, 2D alkaline | 160 hrs. |
| X, Y slope match, manual | 10% |
| HI Alert mode | ✓ |
| Weight (batteries included) | Approx 1.5 kg (3.3 lbs) |
| Dimensions (H x W x D) | 156 mm x 154 mm x 197 mm |
| | (6.1" x 6.06" x 7.75") |
| Warranty | 2 years |
| IP Protection | IP 54 |